

Zenon

ZENON-1s-BF4-IO-W ZENON-1s-BF4-IO-B



IP Technology



4MP Resolution



Intelligent Detection

The ZENON-1s-BF4-IO-W/B are intelligent 4MP compact and sleek IP67 rated Day/Night IR Bullet Cameras. As for optics this camera uses an accurate 3.6mm fixed lens with a 30m IR viewing distance.

The ZENON-1s-BF4-IO-W/B uses an Ambarella chipset which delivers high quality low bandwidth video streaming and can also provide 3 video streams simultaneously. The Ambarella chipset has built in intelligent functions such as Tripwire and the camera also has 120dB WDR as standard.



PERFORMANCE

Image Sensor	CMOS (1/3")
Chipset	Ambarella
Effective Pixels	2688(H) x 1520(V)
Compression	H.264/MJPEG
Resolution	4MP (1-20fps) 3MP (1-25fps)
Streams	3
Bit Rate	32-10Mbps (H.264)

Backlight Compensation	BLC / HLC
Wide Dynamic Range	WDR (120dB)
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Corridor Mode	Yes

LENS

Focal Length	3.6mm
Max Aperture	F2.0
Angle of View	H: 84°

DAY / NIGHT

Min. Illumination	Colour	0.01 Lux @ F2.0
	IR On	0 Lux @ F2.0
Day/Night	Auto (ICR) / Colour / B/W	
IR Distance	30m	

CONNECTIVITY

Ethernet	1 RJ45 (10/100Base-T)
BNC Output (CVBS)	0
Alarm Input	0
Alarm Output	0
Audio Input	0
Audio Output	0
RS-485	0
Memory Slot	0

SOFTWARE

Network Functions	IPv4/ IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
-------------------	---

Smart Phone/Tablet PC / Mac Software	ICRSS Pro / ICView Smart ICRSS / Web Browser Onvif, PSIA
--------------------------------------	--

Intelligent Functions	Tripwire, Intrusion, Abandoned / Missing Object, Scene Change, Audio Detect & Face Detect
-----------------------	---

Trigger Mode	Manual / Auto (alarm triggered)
--------------	---------------------------------

Trigger Event	Recording, Email, Snapshot, Relay
---------------	-----------------------------------

ENVIRONMENTAL

Power Consumption	12vDC / PoE (802.3af) <5W
-------------------	------------------------------

Working Environment Protection	-30°C - 60°C / Less than 95% RH IP67
--------------------------------	---

Dimensions Weight	Ø70 (mm) x 165 (mm) 0.42kg
-------------------	-------------------------------

ACCESSORIES (OPTIONAL)

BASE-B40	Junction Base (White)
MNT-CRM3	Corner Mount (White)
MNT-PM152	Pole Mount (White)



• **European Head Office**
• IC Realtime,
• 12 Knockmitten Lane,
• Western Industrial Estate,
• Dublin 12,
• Ireland

• **UK Office**
• IC Realtime UK
• Surrey Technology Centre,
• 40 Occam Road,
• Guildford GU2 7YG,
• United Kingdom

• **USA Head Office**
• IC Realtime, LLC,
• 3050 N Andrews Ave EXT,
• Pompano Beach,
• FL 33064,
• USA

• **USA West Coast Office**
• IC Realtime West Coast,
• 14180 W Van Buren Street,
• Suite B-105, Goodyear,
• AZ 85338,
• USA