Zenon

ZENON-1s-DF4-IV ZENON-1s-DF4-IV-2.8



The ZENON-1s-DF4-IV(-2.8) is an intelligent 4MP compact and tough IP67/IK10 rated day/night IR Dome Camera. As for optics this camera uses an accurate 3.6 or 2.8mm fixed lens with a 20m IR viewing distance.

The ZENON-1s-DF4-IV(-2.8) uses an Ambarella chipset which delivers high quality low bandwidth video streaming and can also provide 3 video streams simultaneously. The Ambarella chipset has built in intelligent functions such as Tripwire and the camera also has 120dB WDR as standard.

۰.										
	D	E	D	F	n	D	М	Δ	Ν	F
		-			9		L. Y.		L	-

Image Sensor	CMOS (1/3")
Chipset	Ambarella
Effective Pixels Compression Resolution	2688(H) x 1520(V) H.264/MJPEG 4MP (1~20fps) 3MP (1~25fps)
Streams	3
Bit Rate	32~10Mbps (H.264)
Backlight Compensation	BLC / HLC
Wide Dynamic Range	WDR (120dB)
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Corridor Mode	Yes

LENS

Focal Length	3.6mm or 2.8mm
Max Aperture	F1.8 (3.6mm) / F2.0 (2.8mm)
Angle of View	H: 84° (3.6mm) / 106° (2.8mm)

DAY / NIGHT

Min. Illumination	Colour IR On	0.01 Lux @ F2.0 0 Lux @ F2.0
Day/Night IR Distance	Auto (ICR) 20m	/ Colour / B/W



CONNECTIVITY	
Ethernet	1 RJ45 (10/100Base-T)
BNC Output (CVBS)	0
Alarm Input	0
Alarm Output	0
Audio Input	0
Audio Output	0
RS-485	0
Memory Slot	0

SOFTWARE

Network Functions	IPv4/ IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x			
Smart Phone/Tablet PC / Mac Software Onvif	ICRSS Pro / ICView Smart ICRSS / Web Browser Onvif, PSIA			
Intelligent Functions	Tripwire, Intrusion, Abandoned / Missing Ob ject, Scene Change, Audio Detect & Face Detect			
Trigger Mode	Manual / Auto (alarm triggered)			
Trigger Event	Recording, Email, Snapshot, Relay			
European Head Office UK Office				

IC Realtime, 12 Knockmitten Lane, Western Industrial Estate, Dublin 12, Ireland

IC Realtime UK Surrey Technology Centre, 40 Occam Road, Guildford GU2 7YG, United Kingdom

USA Head C IC Realtime Tre, 3050 N And Pompano B FL 33064, USA

USA Head Office IC Realtime, LLC, 3050 N Andrews Ave EXT, Pompano Beach, FL 33064,

ENVIRONMENTAL

USA West Coast Office

- IC Realtime West Coast, 14180 W Van Buren Street, Suite B-105, Goodyear,
- AZ 85338, USA



REALTIME



Power	12vDC / PoE (802.3af)			
Consumption	<5W			
Working Environment	-30°C ~ 60°C / Less than 95% RH			
Protection	IP67 / IK10			
Dimensions	Ø106(mm) x 50.3 (mm)			
Weight	0.35kg			
ACCESSORIES	(OPTIONAL)			
BASE-139-W	Junction Base			
MNT-204-W	Wall Mount			
MNT-PM152	Pole Mount			
MINT-PMI52	Pole Mount			

Specifications subject to change without notice. ©2015 IC Realtime Limited. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.