

# Zenon

## ZENON-1s-DM4-IXV



IP Technology



4MP Resolution



Intelligent Detection



50m IR



Alarm & Audio In/Out

The ZENON-1s-DM4-IXV is an intelligent 4MP long range vandal proof day/night IR Dome Camera. As for optics this camera uses a powerful 2.7-12mm motorised lens with a 50m (max) IR viewing distance.

It uses an Ambarella chipset which delivers high quality low bandwidth video streaming and can also provide 3 video streams simultaneously. The Ambarella chipset has built in intelligent functions such as Tripwire and the camera also has 120dB WDR as standard.



### PERFORMANCE

Image Sensor	CMOS (1/3")
Chipset	Ambarella
Effective Pixels	2688(H) x 1520(V)
Compression	H.264/MJPEG
Resolution	4MP (1-20fps) 3MP (1-25fps)
Streams	3
Bit Rate	32-10Mbps (H.264)

Backlight Compensation	BLC / HLC
Wide Dynamic Range	WDR (120dB)
White Balance	Auto / Manual
Gain Control	Auto / Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Corridor Mode	Yes

### LENS

Focal Length	2.7-12mm Motorised AI Lens
Max Aperture	F1.4
Angle of View	H: 100°- 33°

### DAY / NIGHT

Min. Illumination	Colour	0.01 Lux @ F1.4
	IR On	0 Lux @ F1.4
Day/Night	Auto (ICR) / Colour / B/W	
IR Distance	50m	

### CONNECTIVITY

Ethernet	1 RJ45 (10/100Base-T)
Analogue Port	1
Alarm Input	1
Alarm Output	1
Audio Input	1
Audio Output	1
RS-485	0
Memory Slot	Micro SD (Max 128GB)

### SOFTWARE

Network Functions	IPv4/ IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
-------------------	---

Smart Phone/Tablet PC / Mac Software Onvif	ICRSS Pro / ICView Smart ICRSS / Web Browser Onvif, PSIA
--	--

Intelligent Functions	Tripwire, Intrusion, Abandoned / Missing Object, Scene Change, Audio Detect & Face Detect
-----------------------	---

Trigger Mode	Manual / Auto (alarm triggered)
--------------	---------------------------------

Trigger Event	Recording, Email, Snapshot, Relay
---------------	-----------------------------------

### ENVIRONMENTAL

Power Consumption	12vDC / PoE (802.3af) 10W (Max with IR On and Motorised Lens Operating)
-------------------	--

Working Environment Protection	-30°C - 60°C / Less than 95% RH
Dimensions	IP67 / IK10 Ø159(mm) x 117.9 (mm)
Weight	0.8kg

### ACCESSORIES (OPTIONAL)

PLA-101W	Plate for Wall Mount
MNT-302W	Wall Mount
MNT-PM152	Pole Mount



European Head Office  
IC Realtime,  
12 Knockmitten Lane,  
Western Industrial Estate,  
Dublin 12,  
Ireland

UK Office  
IC Realtime UK  
Surrey Technology Centre,  
40 Occam Road,  
Guildford GU2 7YG,  
United Kingdom

USA Head Office  
IC Realtime, LLC,  
3050 N Andrews Ave EXT,  
Pompano Beach,  
FL 33064,  
USA

USA West Coast Office  
IC Realtime West Coast,  
14180 W Van Buren Street,  
Suite B-105, Goodyear,  
AZ 85338,  
USA