

# FUSION-2s-216

The FUSION-2s-216 is a versatile 16 channel 1U (desktop) Tri-Tech recorder that combines 3 video technologies (IP, HDCVI & analogue).

This 16 channel recorder with internal capacity for 2 hard drives has 16 self-adaptive BNC inputs, that can process either an SD analogue or a HDCVI signal. Its embedded HD processor can also facilitate 2 IP channels.

Using the latest HD over coax technology (HDCVI) combined with powerful networking capabilities; this future proof recorder is ideally suited for existing coaxial & Cat 5 installations, saving you valuable deployment time whilst delivering 720P/1080P recording.

#### PERFORMANCE

Resolution	IP HDCVI Analogue	1080P 1080P 720P 960H	(1-25fps) (1-15fps) (1-25fps) (1-25fps)
IP Recording		8Mbps	
Processor		Dual Core Embedded	
Video Compression		H.264, MJPEG	
Audio Compression		G711A	

### SOFTWARE

OS	Embedded Linux (ICR OS)
Video Detection	Motion Detection, Video
	Loss & Camera Masking
Smart Search	Yes
Simultaneous Playback	All Channel
Max User Access	128
Network Functions	Alarm Server, DDNS, DHCP,
Hetwork Functions	DNS, Email, FTP, HTTP, IP
	Filter, IPv4, IPv6, PPPoE,
	RTSP, SMTP, TCP/IP, UDP,
	UPnP
IPC Support	Onvif, Axis, Bosch, Hikvision,
	Panasonic, Pelco, Samsung,
	Sony and many more
Smart Phone / Tablet	ICRSS Pro & ICView
PC / Mac Software	SmartICRSS & Web Browser
Push Notifications	Yes
ICDDNS	Yes
P2P	Yes
Extra Stream	Yes
Onvif	Yes
ARC Integration	Yes
, and antegration	



CONNECTIVITY	
Total Video Channels IP Channels HDCVI Channels Analogue Channels	16 2 16 16
Audio Input (RCA) Audio Output (RCA) 2 Way Audio Supported	4 1 Yes
Alarm Inputs Alarm Outputs	16 3
HDMI VGA BNC (Master)	1 1 0
PoE IPC Ports 10/100M RJ45 Port 10/100/1000M RJ45 Port	0 0 1
RS-485 RS-232 USB Ports	1 n/a 2 (1 Rear)

STORAGE		
SATA Ports	2	
RAID	n/a	
eSATA Port	0	
Backup Methods	USB & Network	

#### ENVIRONMENTAL

Case Size Dimensions (mm) Power Supply Power Consumption Working Environment Weight Certification 1U Desktop 375 (W) x 285 (D) x 55 (H) 12V DC / 5 Amp 15W (without HDD) -10°C-+55°C/10%-90%RH/ 86-106kpa 2.35KG (without HDD) CE, FCC



## European Head Office

12 Knockmitten Lane, Western Industrial Estate, Dublin 12, Ireland UK Office

IC Realtime UK

40 Occam Road,

United Kingdom

Guildford GU2 7YG,

Surrey Technology Centre,

## USA Head Office

3050 N Andrews Ave EXT, Pompano Beach, FL 33064, USA

#### USA West Coast Office

IC Realtime West Coast, 14180 W Van Buren Street, Suite B-105, Goodyear,

AZ 85338,

USA